SDS Number: 1700665 SAP Number: Revision Date: 12/6/2024



Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control: In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-50531-35 2-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.Los Datos de Serguridad pueden obtenerse en Espanol si lo riquiere.

Product Name: Alex Plus Acrylic Latex Caulk Plus Silicone - Revision Date: 12/6/2024

All Colors

Product UPC Number: 070798742437, 070798742338, Supercedes Date: 4/12/2022

070798742772, 070798742253

Product Use/Class: Caulking Compound SDS No: 1700665

Manufacturer: DAP Canada Imported by: DAP Canada

475 Finchdene Square Unit 5 475 Finchdene Square Unit 5

Scarborough, Ontario M1X 1B7
888-327-8477 (non - emergency matters)
Scarborough, Ontario M1X 1B7
888-327-8477 (non - emergency

matters)

SDS Coordinator: MSDS@dap.com

SDS Coordinator: Emergency Telephone: 1-800-535-5053, MSDS@dap.com

Emergency Telephone: 1-800-535-5053, MSDS@dap.com 1-352-323-3500

Emergency Telephone: 1-800-535-5053, 1-352-323-3500

Preparer: Regulatory and Environmental Affairs

2. Hazards Identification

SDS Number: 1700665 SAP Number: Revision Date: 12/6/2024

GHS Classification Carc. 1A, STOT RE 1

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

63% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Carcinogenicity, category 1A H350 May cause cancer.

STOT, repeated exposure, category 1 H372 Causes damage to organs through prolonged or repeated exposure.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container.

GHS SDS PRECAUTIONARY STATEMENTS

P270 Do no eat, drink or smoke when using this product.

3. Composition/Information on Ingredients

 Chemical Name
 CAS-No.
 Wt. %
 GHS Symbols
 GHS Statements

 Limestone
 1317-65-3
 30-60
 GHS 08
 H350-372

 Lubricating petroleum oil
 72623-86-0
 5-10
 GHS 07
 H332

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: None Known.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate. Dispose of saturated absorbent or cleaning materials appropriately. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain federal and state requirements.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with	Occupational	Exposure	I imits
III WI CUICI ILO WILI	Occupational		

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Limestone	N.E.	N.E.	15 mg/m3 TWA to dust, 5 mg/m3 TW respirable fraction	Α
Lubricating petroleum oil	N.E.	N.E.	N.Ė.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

SDS Number: 1700665 Revision Date: 12/6/2024 SAP Number:

9. Physical and Chemical Properties

Color: Colored

Appearance: Paste Odor: Very Slight Ammonia **Physical State:** Solid

Density, g/cm3: 1.58

Freeze Point, °C: pH: Not Established Between 7.0 and 12.0 Solubility in Water: Not Established Not Established Viscosity (mPa.s): Decomposition Temperature, °C: Not Established Partition Coeff., n-octanol/water: Not Established

Odor Threshold:

Flash Method:

Not Established

Not Applicable

N.E.

Boiling Range, °C: Explosive Limits, %: N.A. Mixture w/o a

constant boiling point. Auto-Ignition Temperature, °C Not Established Minimum Flash Point, °C: Water - based, does Vapor Pressure, mmHg: Not Established

not flash.

Evaporation Rate: Slower Than n-Butvl Acetate

Vapor Density: Heavier Than Air

Combustible Dust: Does not support combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No. 1317-65-3	<u>Chemical Name</u>	Oral LD50	<u>Dermal LD50</u>	Vapor LC50
	Limestone	6450 mg/kg Rat	N.I.	N.I.
72623-86-0	Lubricating petroleum oil	>5000 mg/kg Rat	>2000 mg/kg Rabbit	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number: N.A.

DOT Proper Shipping Name: Not Regulated

DOT Technical Name: N.A.
DOT Hazard Class: N.A.
Hazard SubClass: N.A.
Packing Group: N.A.

15. Regulatory Information

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

SDS Number: 1700665 SAP Number: Revision Date: 12/6/2024

16. Other Information

Revision Date: 12/6/2024 Supersedes Date: 4/12/2022

Reason for revision: Product Composition Changed

Substance and/or Product Properties Changed in Section(s):

02 - Hazards Identification05 - Flammability Information

08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information 11 - Toxicological Information 14 - Transportation Information

15 - Regulatory Information16 - Other Information

Substance Regulatory CAS Number Changed Substance Hazardous Flag Changed Substance Hazard Threshold % Changed

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health: Flammability: Reactivity: Personal Protection:

1 1 0 X

VOC Less Water Less Exempt Solvent, g/L: 10.3

VOC Material, g/L: 7

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 0.02

VOC Actual, Wt/Wt%: 0.5

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H332 Harmful if inhaled. H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.