



## Crack Filler for Asphalt (cartridge)

### UPDATE

---

#### January 10<sup>th</sup>, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: [techniseal.com](http://techniseal.com)

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Driveways, commercial parking lots, pedestrian areas, etc.

### PROPERTIES

---

- Stops deterioration caused by water and frost
- Adherent, flexible and durable

### DESCRIPTION

---

This Techniseal<sup>®</sup> Crack Filler for asphalt is a flexible compound designed to repair cracks 1 cm wide or less. Containing a high percentage of solids, it dries without losing volume. It protects against damage caused by water and freeze-thaw cycles. Easy to apply, it adheres strongly to inner walls of cracks and remains flexible to allow for asphalt movement.

**Note :** This product is formulated for cracks 1 cm ( 1/2") wide or less. For cracks wider than 1 cm, use Techniseal Acrylic Crack Filler (142-711).

### DIRECTIONS

---

#### SURFACE PREPARATION

Clean cracks with a water jet; let dry completely. Fill deep cracks with fine sand to within 2 cm (3/4") of the surface.

#### APPLICATION

Content's temperature must be above 12°C; however, product can be applied at a lower temperature. Cut nozzle at an angle to the desired diameter. Fill cracks to surface level. Let dry for 24 hours before applying sealant or allowing traffic on the surface. For a uniform appearance and maximum protection, apply a Protector for Asphalt from Techniseal<sup>®</sup> to the entire surface.

**NOTE:** Store at a temperature above 15°C.

## PACKAGING

Product code	Retail Size	Units per box	Units per pallet
70978056 (142-731)	300 mL	20	1140

## WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN**

## TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

Manufacturer's liability is limited to the replacement of the product. A proof of purchase will be required for any claim.