



NEW! MORE COMPACT CONVECTOR.

Modern, simple and discreet design to match any decor.


Top air outlet for rapid, even heat distribution throughout the room.

Convector

QUICK AND EASY INSTALLATION



Built-in single-screw wire connector on the back for quick junction box access.



Unpainted wall mounting bracket included.

A COMPACT UNIT

This is our most compact natural convection unit. It provides you with greater flexibility when arranging your room.

CHOICE OF CONTROLS

Consumers can choose from two control options:



Built-in electronic thermostat



Electronic wall thermostat

(Not offered by Global Commander)

(Thermostat shown here as an example only)

IDEAL FOR

Office, bedroom, living room, kitchen, basement, entrance hall.



Convector

Watts	Heats an area of about ¹	
	sq. ft.	sq. m
500	50	4.65
1000	100	9.29
1500	150	13.94
2000	200	18.58

¹ Intended as a guide only. These calculations are based on a room with an 8 foot ceiling, R12 wall insulation and R20 ceiling insulation. The suggested heating capacity would then be able to keep the room temperature at 21 °C (70 °F) when the outdoor temperature is at -25 °C (-13 °F). The heating capacity required will vary depending on the area and volume of the room, the layout and orientation of the residence, its geographic location, type of construction, insulation and airtightness levels, as well as the size, type and orientation of the windows, etc.



Quiet unit



Easy to use



Sturdy construction