

SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint Light Grey

SECTION 1. IDENTIFICATION

Product Identifier	SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint	Light Grey
Product Family	Water Thinned Paint	
Recommended Use	Coating.	
Restrictions on Use	Not applicable.	
Manufacturer/Supplier Identifier	Denalt Paints, 8620 Pascal Gagnon, St-Leonard, Quebec, H1P 1Z1	
Emergency Phone No.	Peinture DENALT Paints, 514-328-2727 / 514-691-3533	
SDS No.	0375	
Date of Preparation	mai 02, 2023	

SECTION 2. HAZARD IDENTIFICATION

Classification

Not classified under any hazard class.

Label Elements

Not applicable

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Titanium dioxide	13463-67-7	Max 10	Pigment White no. 6	
Nepheline syenite	37244-96-5	Max 10		
3-Iodo-2-Propyl ButylCarbamate	55406-53-6	Max 0.2		
Propionic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	25265-77-4	Max 3		
Carbon black	1333-86-4	Max 0.2		

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes.

Eye Contact

Rinse the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes, while holding the eyelid(s) open.

First-aid Comments

Product Identifier:	SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint	SDS No.:	0375
Date of Preparation:	mai 02, 2023		
Date of Last Revision:	juin 17, 2021	Page	01 of 06

Get medical advice or attention if you feel unwell or are concerned.

Most Important Symptoms and Effects, Acute and Delayed

Not applicable.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Not combustible. Use extinguishing agent suitable for surrounding fire.

Unsuitable Extinguishing Media

Not applicable.

Specific Hazards Arising from the Product

Does not burn.

Not known to generate any hazardous decomposition products in a fire.

Special Protective Equipment and Precautions for Fire-fighters

No special precautions are necessary.

Chemical protective clothing (e.g. chemical splash suit) and positive pressure SCBA may be necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Use the personal protective equipment recommended in Section 8 of this safety data sheet.

Environmental Precautions

It is good practice to prevent releases into the environment.

Methods and Materials for Containment and Cleaning Up

No special clean-up methods are necessary.

Other Information

None known.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling.

Conditions for Safe Storage

Protect from conditions listed in Conditions to Avoid in Section 10 (Stability and Reactivity).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Titanium dioxide	10 mg/m3 Not established					
Carbon black			3.5 mg/m3			

Consult local authorities for provincial or state exposure limits.

Appropriate Engineering Controls

The hazard potential of this product is relatively low. General ventilation is usually adequate.

Individual Protection Measures

Eye/Face Protection

Product Identifier: SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint
Date of Preparation: mai 02, 2023
Date of Last Revision: juin 17, 2021

SDS No.: 0375

Page 02 of 06

Not required if product is used as directed.

Skin Protection

Not required, if used as directed.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Grey liquid. Particle Size: Not available
Odour	Ammonia-like
Odour Threshold	Not available
pH	8.5 - 9.5
Melting Point/Freezing Point	Not available (melting); 0 °C (freezing)
Boiling Range	100 °C
Flash Point	Not applicable
Evaporation Rate	Not available
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	Not applicable (upper); Not applicable (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	1.18 - 1.22
Solubility	Soluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not applicable
Decomposition Temperature	Not available
Viscosity	Not applicable (kinematic); Not applicable (dynamic)

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Temperatures below 0 °C

Incompatible Materials

Not applicable.

Hazardous Decomposition Products

Not applicable.

SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

Likely Routes of Exposure

Product Identifier: SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint
Date of Preparation: mai 02, 2023
Date of Last Revision: juin 17, 2021

SDS No.: 0375

Page 03 of 06

Skin contact; eye contact; ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Titanium dioxide	> 6820 mg/m3 (rat) (4-hour exposure) (dust)	Not available	> 10000 mg/kg (rabbit)
Nepheline syenite	Not available	Not available	Not available
Carbon black	6 750 mg/m3 (rat) (4-hour exposure) (dust)	> 15 400 mg/kg (rat)	3 000 mg/kg (rabbit)
Propionic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	> 3.55 mg/L (rat) (4-hour exposure)	6500 mg/kg (rat) (4-hour exposure)	> 15200 mg/kg (rabbit)

Skin Corrosion/Irritation

Human experience shows very mild irritation.

Serious Eye Damage/Irritation

May cause mild irritation based on information for closely related chemicals.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

No information was located.

Skin Absorption

No information was located.

Ingestion

May be harmful If large amounts are swallowed.

Aspiration Hazard

Not known to be an aspiration hazard.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No information was located.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Titanium dioxide	Group 2B	A4		Listed
3-Iodo-2-Propyl ButylCarbamate		Not Listed		
Carbon black	Group 2B	A4		Listed
Propionic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	Not Listed			

Even if IARC considers titanium dioxide as being potentially cancerogenous for humans, this conclusion should be understood as follows: " We think that the use of titanium dioxide in products where it is bonded to other materials, like in the case of paint, do not cause significant exposure to titanium dioxide." Even if IARC considers carbon black as being potentially cancerogenous for humans, this conclusion should be understood as follows: We think that the use of carbon black in products where it is bonded to other materials, like in the case of paint, do not cause significant exposure to carbon black.

Key to Abbreviations

Group 2B = Possibly carcinogenic to humans. OSHA = US Occupational Safety and Health Administration. Listed.

Reproductive Toxicity

Development of Offspring

Product Identifier:	SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint	SDS No.:	0375
Date of Preparation:	mai 02, 2023		
Date of Last Revision:	juin 17, 2021	Page	04 of 06

No information was located.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

Other Information

None known

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Titanium dioxide	> 1000 mg/L (Pimephales promelas (fathead minnow); 96-hour)		> 61 mg/L (Pseudokirchneriella subcapitata (algae); 72-hour)	> 100 mg/L (Daphnia magna (water flea); 48-hour)
3-Iodo-2-Propyl ButylCarbamate	0.2 mg/L (Pimephales promelas (fathead minnow); 96-hour)	(Mysidopsis bahia (opossum shrimp))	40 mg/L (Daphnia magna (water flea))	
Carbon black	> 1 000 mg/L (96-hour)	> 5 600 mg/L (Daphnia magna (water flea); 48-hour)		
Propionic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol	33 mg/L (Pimephales promelas (fathead minnow); 96-hour)	147.8 mg/L (Daphnia magna (water flea); 48-hour)		15 mg/L (Pseudokirchneriella subcapitata (algae); 72-hour)

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

This product is a non-hazardous waste. The required hazard evaluation of the waste and compliance with the applicable hazardous waste laws are the responsibility of the user.

SECTION 14. TRANSPORT INFORMATION

Not regulated under Canadian TDG regulations. Not regulated under US DOT Regulations. Not regulated under IATA Regulations.

Environmental Hazards Not applicable

Special Precautions Not applicable

Transport in Bulk according to International Maritime Organization Instruments

Not applicable

Other Information Not regulated under IMDG / IMO

Product Identifier: SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint
Date of Preparation: mai 02, 2023
Date of Last Revision: juin 17, 2021

SDS No.: 0375

Page 05 of 06

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

None known.

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1	Flammability - 0	Instability - 0
	Based on	Titanium dioxide	
SDS Prepared By	Product Stewardship Dept		
Phone No.	514-328-2727		
Date of Last Revision	juin 17, 2021		
References	CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS). Registry of Toxic Effects of Chemical Substances (RTECS®) database. Dassault Systèmes/BIOVIA ("BIOVIA"). Available from Canadian Centre for Occupational Health and Safety (CCOHS).		

Product Identifier: SXPLDP55-XX Acrylic Epoxy fortified Cement & Garage Floor Paint
Date of Preparation: mai 02, 2023
Date of Last Revision: juin 17, 2021

SDS No.: 0375

Page 06 of 06