



SOLAR BLANKET LIMITED WARRANTY, INSTALLATION AND USE INFORMATION

RBF International Ltd. (hereinafter the "Distributor" of the NEPTUNE brand) warrants to the original purchaser that the Distributor at its sole discretion, subject to the warranty provisions, will replace a NEPTUNE solar blanket that it deems to be a manufacture defect. It is imperative that the purchaser follows the provided installation instruction and use information; non-compliance voids the warranty. The only conditions covered under this warranty are delamination and seam failure. The Distributor will reject warranty requests resulting from high chlorine and/or alkalinity levels, blanket abuse, negligence, and other causes of product failure. Blistering, flaking, and delamination are the most visible effects of Chemical Damage, and any such defects void the warranty.

3-Season Warranty with 1 season full

The claimant shall pay the following percent of list price at the time of the claim for replacement cover plus tax and freight.

0 %	1 st season
50 %	2 nd Season
90 %	3 rd Season

The solar blanket must be returned to the retailer from whom it was purchased, along with the original invoice. **if a manufacturing defect is found during installation or in the following days. Otherwise, please refer to the « IMPORTANT INFORMATION » page below.**

The returned solar blanket must be shipped prepaid.

This warranty is only conditions covered under this warranty are delamination and seam failure.

NOTE: Solar covers must never be installed on a pool immediately after a pool shock or chlorine treatment. The concentrated chemical product will destroy the solar blanket. A minimum delay of 24 hours after any chemical treatment must be allowed before reinstalling the solar blanket on the pool. This warranty will be void if the solar blanket for damaged caused by excess chemical use to respect this delay. Delamination of the solar blanket resulting from improper storage or exposure to the sun is not covered by this warranty.

INFORMATIONS IMPORTANTES

NE PAS RETOURNER LA TOILE SOLAIRE AU DÉTAILLANT NI À COVERTECH APRÈS L'INSTALLATION DE LA TOILE SUR VOTRE PISCINE. LES CLOQUES, L'ÉCAILLAGE ET LA DÉLAMINATION SONT LES EFFETS LES PLUS VISIBLES DES DOMMAGES CHIMIQUES ET TOUT DÉFAUT DE CE TYPE ANNULE LA GARANTIE.

LA GARANTIE EST ANNULÉE DANS LES CIRCONSTANCES SUIVANTES :

- L'UTILISATION D'UNE QUANTITÉ EXCESSIVE DE PRODUITS CHIMIQUES À TOUT MOMENT.
- L'UTILISATION D'UN SYSTÈME DE GÉNÉRATION DE CHLORE AU SEL.
- L'EXPOSITION DE LA TOILE AUX RAYONS DU SOLEIL LORSQU'ELLE N'EST PAS UTILISÉE.
- LA TOILE EST PLACÉE SUR LA PISCINE DANS LES 24 HEURES SUIVANT LA CHLORATION.
- LA TOILE N'EST PAS RINCÉE DES PRODUITS CHIMIQUES APRÈS AVOIR ÉTÉ RETIRÉE DE LA PISCINE.
- LA TOILE EST TRAÎNÉE SUR LA TERRASSE.

LA RÉSINE DE BASE DE LA TOILE SOLAIRE EST LE POLYÉTHYLÈNE. LES FONCTIONS PRINCIPALES DE CE PRODUIT SONT L'AUGMENTATION DE LA TEMPÉRATURE DE L'EAU, LA RÉDUCTION DE L'ÉVAPORATION DE L'EAU ET LA DIMINUTION DE LA PERTE D'EFFICACITÉ CHIMIQUE.

CONSULTEZ LA GARANTIE POUR DES INFORMATIONS SUR L'UTILISATION ET LES DÉTAILS DE LA GARANTIE.

IMPORTANT INFORMATION

DO NOT RETURN SOLAR BLANKET TO DEALER OR TO COVERTECH POST PLACEMENT OF COVER ON YOUR SWIMMING POOL. BLISTERING, FLAKING AND DELAMINATION ARE THE MOST VISIBLE EFFECTS OF CHEMICAL DAMAGE AND ANY SUCH DEFECTS VOID THE WARRANTY.

WARRANTY VOID UNDER THE FOLLOWING CIRCUMSTANCES:

- USE OF EXCESSIVE CHEMICALS AT ANY TIME.
- USE OF A SALTWATER CHLORINATION SYSTEM.
- COVER IS EXPOSED TO SUNLIGHT WHEN NOT IN USE.
- COVER BEING PLACED ON THE POOL WITHIN 24 HOURS OF CHLORINATION
- COVER IS NOT RINSED OF CHEMICALS POST REMOVAL FROM POOL.
- COVER BEING DRAGGED ACROSS DECK.

THE SOLAR COVER'S BASE RESIN IS POLYETHYLENE. THIS PRODUCT'S PRIMARY FUNCTIONS ARE INCREASING WATER TEMPERATURE, REDUCING WATER EVAPORATION, AND LESSENING CHEMICAL LOSS.

SEE WARRANTY FOR INFORMATION ON USE AND WARRANTY DETAILS.

INSTRUCTIONS FOR USE AND INSTALLATION

INSTALLATION

Your solar blanket must be installed on the pool with the bubble side down. If trimming is necessary, allow the blanket to rest on the pool for 24 hours before trimming. Initial trimming should be slightly larger to allow for sun exposure. Precision trimming is necessary to ensure a custom fit. Be very careful not to cut the liner if you have a vinyl lined pool. The blanket should not overlap the pool sidewall to prevent wind infiltration under the blanket.

REMOVAL

To remove the blanket, two people can pull 3 to 4 feet at a time and fanfold the blanket in an accordion fashion outside of the pool. To avoid handling damage, do not drag blanket across coping or rough deck. Once off the pool, the blanket must be kept in the shade or covered with a protective cover sheet (not included). An uncovered solar blanket (when not in use) exposed to the sun will result in extensive damage to the blanket and void the warranty.

IMPORTANT MAINTENANCE TIPS

You should monitor the level of chlorine below 3 PPM. When shocking pool, keep the blanket off for at least 24 hours. Damage caused by excessive chlorine exposure (patches of brittle, flaked bubbles) will void the Warranty.

You can clean your cover using a mild detergent, water and a soft brush. A clean cover should perform much better. Store your cover away from rodents and avoid areas where temperature can reach 120°F.

PERFORMANCE

When used properly, your solar blanket should provide maximum heat by day and insulate by night. Temperature could rise by 10°F or more. The blanket should keep pool cleaner, reduce chemical usage and result in water conservation.