SAFETY DATA SHEET

1. Identification

Product identifier	**Glisten Washing Machine Cleaner & Freshener**
Other means of identification	Not available.
Recommended use	Freshener and Cleaner
Recommended restrictions	None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name	Iron Out dba Summit Brands
Address	6714 Pointe Inverness Way, Suite 200 Fort Wayne, IN 46804-7935 United States
Telephone	260-483-2519
E-mail	Not available.

Emergency phone number	1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazard identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	

Label elements

Signal word	Warning
Hazard statement	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention	Wash thoroughly after handling. Wear protective gloves and eye protection. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing dust.
Response	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	Store away from incompatible materials.
Disposal	Dispose of container in accordance with local, regional, national and international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Benzoic acid, phenylmethyl ester		120-51-4	0.1-1*
Calcium silicate		1344-95-2	0.1-1*
Citric Acid		77-92-9	30-60*
Octadecanoic acid, sodium salt		822-16-2	0.1-1*
Oils, orange, sweet		8008-57-9	0.1-1*
Polyethylene glycol		25322-68-3	3-7*
Sodium carbonate		497-19-8	7-13*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Skin contact

IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is convulsing. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Wear rubber gloves and chemical splash goggles. Keep out of reach of children.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical powder. Carbon dioxide. Water Fog.

Unsuitable extinguishing media

None known.

Specific hazards arising from the chemical

Firefighters should wear a self-contained breathing apparatus.

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing including self-contained breathing apparatus.

Fire-fighting equipment/instructions

In the event of fire, cool tanks with water spray. Cool containers with flooding quantities of water until well after fire is out.

Specific methods

Cool containers exposed to flames with water until well after the fire is out.

Hazardous combustion products

May include and are not limited to: Oxides of carbon. Oxides of sulfur.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of dust from the spilled material. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Absorb spillage to prevent material damage. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner equipped with HEPA filter. Minimize dust generation and accumulation. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not get in eyes, on skin or on clothing. Avoid breathing dust. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Use only with adequate ventilation. Avoid prolonged exposure. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. Keep container tightly closed.

Conditions for safe storage, including any incompatibilities Store in a closed container away from incompatible materials. Keep only in the original container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place.

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Calcium silicate (CAS 1344-95-2)	TWA	10 mg/m3
Octadecanoic acid, sodium salt (CAS 822-16-2)	TWA	10 mg/m3

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Octadecanoic acid, sodium salt (CAS 822-16-2)	TWA	10 mg/m3	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	TWA	1 mg/m3	Inhalable fraction.
Octadecanoic acid, sodium salt (CAS 822-16-2)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Calcium silicate (CAS 1344-95-2)	TWA	10 mg/m3
Octadecanoic acid, sodium salt (CAS 822-16-2)	TWA	10 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	TWA	10 mg/m3	Total dust.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Calcium silicate (CAS 1344-95-2)	15 minute	20 mg/m3
	8 hour	10 mg/m3
Octadecanoic acid, sodium salt (CAS 822-16-2)	15 minute	20 mg/m3
	8 hour	10 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	TWA	1 mg/m3	Inhalable fraction.
Octadecanoic acid, sodium salt (CAS 822-16-2)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium silicate (CAS 1344-95-2)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Polyethylene glycol (CAS 25322-68-3)	TWA	10 mg/m3	Aerosol.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear chemical goggles.

Skin protection

Hand protection Rubber gloves. Confirm with a reputable supplier first.

Other Wear appropriate chemical resistant clothing. As required by employer code.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not applicable.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance Solid.

Physical state Solid.

Form Tablet.

Color Peach.

Odor Spring rain

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Pour point Not available.

Specific gravity Not available.

Partition coefficient (n-octanol/water) Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	Reacts vigorously with alkaline material or metals. This product may react with reducing agents. Do not mix with other chemicals.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Not corrosive to steel or non-clad aluminum based on test data for similar product. Strong oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxides of sulfur.

11. Toxicological information

Routes of exposure	Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion	May cause stomach distress, nausea or vomiting.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Benzoic acid, phenylmethyl ester (CAS 120-51-4)		
Acute		
Dermal		
LD50	Rabbit	> 2 ml/kg, 4 Hours, ECHA
		4000 mg/kg, ECHA
	Rat	4000 mg/kg, HSDB
Inhalation		
LC50	Not available	
Oral		
LD50	Cat	2240 mg/kg, HSDB
	Dog	> 22440 mg/kg, HSDB
	Guinea pig	1121 mg/kg, HSDB
	Mouse	3253 mg/kg, ECHA
		1400 mg/kg, HSDB
	Rabbit	1680 mg/kg, HSDB
	Rat	> 2000 mg/kg, ECHA
		1700 mg/kg, HSDB

Components	Species	Test Results
Calcium silicate (CAS 1344-95-2)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Rat	> 2.6 mg/L, 4 Hours, ECHA
Oral		
LD50	Rat	> 5000 mg/kg, ECHA
Citric Acid (CAS 77-92-9)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours, ECHA
Inhalation		
LC50	Not available	
Oral		
LD50	Mouse	5400 mg/kg, ECHA
	Rat	11700 mg/kg, ECHA
Octadecanoic acid, sodium salt (CAS 822-16-2)		
Acute		
Dermal		
LD50	Rabbit	> 3000 mg/kg, CCOHS
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	> 5000 mg/kg, CCOHS
Oils, orange, sweet (CAS 8008-57-9)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg, ECHA
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	> 5000 mg/kg, ECHA
Polyethylene glycol (CAS 25322-68-3)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, ECHA
Inhalation		
LC50	Not available	
Oral		
LD50	Rat	5010 mg/kg, ECHA
		4300 mg/kg, ECHA
Sodium carbonate (CAS 497-19-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, ECHA
Inhalation		
LC50	Guinea pig	800 mg/m3, 2 Hours, ECHA
	Mouse	1200 mg/m3, 2 Hours, ECHA
	Rat	2300 mg/m3, 2 Hours, ECHA
Oral		
LD50	Rat	2800 mg/kg, ECHA, HSDB

Skin corrosion/irritation Causes skin irritation.

Exposure minutes Not available.

Erythema value Not available.

Oedema value Not available.

Serious eye damage/eye irritation Causes serious eye irritation.

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening value Not available.

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Calcium silicate (CAS 1344-95-2) Irritant
Octadecanoic acid, sodium salt (CAS 822-16-2) Irritant

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

Mutagenicity Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity Non-hazardous by WHMIS/OSHA criteria.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Reproductive toxicity Non-hazardous by WHMIS/OSHA criteria.

Teratogenicity Non-hazardous by WHMIS/OSHA criteria.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components		Species	Test Results
Citric Acid (CAS 77-92-9)			
Acute			
Crustacea	EC50	Daphnia magna	120 mg/L, 72 hr
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	1516 mg/L, 96 hr
Polyethylene glycol (CAS 25322-68-3)			
Aquatic			
Fish	LC50	Atlantic salmon (Salmo salar)	> 1000 mg/L, 96 hours
Sodium carbonate (CAS 497-19-8)			
Crustacea	EC50	Daphnia	265 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	156.6 - 298.9 mg/L, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	300 mg/L, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Mobility in general Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions	Not applicable
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance	No
SARA 311/312 Hazardous chemical	Yes
Classified hazard categories	Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - Minnesota Haz Subs: Listed substance

Calcium silicate (CAS 1344-95-2)	Listed.
Octadecanoic acid, sodium salt (CAS 822-16-2)	Listed.
Polyethylene glycol (CAS 25322-68-3)	Listed.

US - Texas Effects Screening Levels: Listed substance

Benzoic acid, phenylmethyl ester (CAS 120-51-4)	Listed.
Calcium silicate (CAS 1344-95-2)	Listed.
Citric Acid (CAS 77-92-9)	Listed.
Oils, orange, sweet (CAS 8008-57-9)	Listed.
Polyethylene glycol (CAS 25322-68-3)	Listed.
Sodium carbonate (CAS 497-19-8)	Listed.

US. Massachusetts RTK - Substance List

Calcium silicate (CAS 1344-95-2)

US. New Jersey Worker and Community Right-to-Know Act

Calcium silicate (CAS 1344-95-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium silicate (CAS 1344-95-2)

US. Rhode Island RTK

Calcium silicate (CAS 1344-95-2)

US. California Proposition 65

This product is not subject to warning labeling under the California Proposition 65 regulation.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0



Disclaimer The data contained in this material safety data sheet was obtained from sources that were technically accurate, reliable, and state of the art when this document was prepared. If data was unavailable to complete certain sections, the absence of that data is identified in this document. Because the supplier cannot know the exact circumstances during actual use of this product, other hazards, exposure scenarios, disposal considerations, and regulations may apply and it is the responsibility of the user to read and understand the product label and this document before use. Do not use the product for purposes other than those stated in Section 1.

Issue date 03-April-2020

Version # 03

Effective date 03-April-2020

Prepared by Dell Tech Laboratories Ltd. Phone: (519) 858-5021

Further information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Other information Redbook revision # 1, 3/31/20