

MSL

563

Adhesive for soundproofing membranes, engineered wood, parquet and vinyl flooring



Installation Guide

COVERAGE:

Approximatively 1.8 m² / L.

PREPARATION:

Subfloor must be structurally sound, linear, porous, clean, dry and free of contaminants. The adhesive and the flooring material (unwrapped) must be at room temperature (20° C) 24 hours prior to, during and following installation. For best results, moisture content of the wood should ideally range between 8% and 12%; concrete must be completely cured, and free from moisture and hydrostatic pressure.

APPLICATION:

Stir before using. Spread adhesive with a 5 mm (3/16") V notch trowel held at a 45° angle. Apply adhesive evenly on surface that will be covered in approximately 20 minutes. Leave 6 mm (1/4") minimum space uncovered along the walls and permanent structures for normal expansion. The finished installation should be rolled immediately in both directions with a 100 Lbs roller. Let dry 24 hours before allowing heavy foot traffic or moving furniture.

ATTENTION:

Refer to flooring and/or soundproofing membrane manufacturer's recommendations for expansion space requirements and detailed installation instructions. Room temperature must be kept at 20°C and at relative humidity between 35%-55% one week before the installation and thereafter. For indoor use only. For basement floors or areas below grade, a subfloor should be built over a vapour barrier.

CLEAN UP:

Wash hands, tools as well as excess adhesive with warm soapy water before product dries. If adhesive has dried, clean cautiously with mineral spirits. On bonded materials, scrape and sand excess adhesive.

STORAGE:

Shelf life of this product is 1 year in original unopened container stored at room temperature. This product is stable from freeze/thaw to -10°C.

PRECAUTIONS:

This product is not classified dangerous as per the Consumer Chemicals and Containers Regulations (CCCR). Not a regulated product as per the Workplace Hazardous Materials Information System (WHMIS). For further details, see Material Safety Data Sheet.

ENVIRONMENT:

Meets VOC standards for low emissions adhesives and sealants in place at date of production.

WARRANTY:

Surface conditions, application, storage and transportation of product are not in the manufacturer's control; any liability is strictly limited to product replacement. Refer to the relevant flooring and / or soundproofing membrane manufacturer's recommendations for compatibility with this product.

For additional information :
Customer support : 1 (800) 561-4279
Website : www.mslfibre.com

infoplus@mslfibre.com

Developed in
Canada 