

### Technical data sheet

#### Tonic for wood and laminate floors

##### PHYSICAL PROPERTIES

Color	Translucent white
Solid content (w/w)	20% ± 1%
pH	9,5 ± 0,2
Resistance to chemicals	Excellent
Resistance to abrasion (Taber test)	N. A.
VOC	323 g/L
Flash point	N.A.
Luster 60°	Semi-gloss: 40%
Freeze / thaw stability	Keep from freezing
Drying time (depending on conditions)	Light traffic: 2 to 4 hours • Furniture: 24 hours Carpets and rugs: 28 days • First wet cleaning: 28 days
Viscosity	23 to 25 seconds (Zahn #2)
Density	1,03 - 1,04 kg/L

##### TECHNICAL DATA

Coverage	400 sq.ft. (37 m <sup>2</sup> ) / liter (depending on conditions)
Size available	1 L
Shelflife	12 months (when kept in its original container)
Tools	Finitec applicator or 3/8" (10 mm) roller
Tools clean-up	Water
Storage	Dry and well-ventilated area
Waste disposal	Recycle if possible (Consult local authorities)

##### FIRST AID AND WARNING

Contains polymers, glycol ethers, tension-active agents. If swallowed, call a Poison Control Centre or a physician immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. Seek a physician. If on skin, rinse well with water. Seek a physician if problems occur. AVOID CONTACT WITH EYES OR SKIN. KEEP OUT OF REACH OF CHILDREN.

