

ULTRA PRIME

TECHNICAL DATA SHEET | CANAC ULTRA PRIME 967-031



PRODUCT DESCRIPTION

Stain killer primer and undercoat ULTRAPRIME is specifically designed to block stains impossible to hide with standard latex primer. It also adheres to rust and multiple surfaces.

IDEAL FOR

New, previously painted or varnished interior and exterior surfaces.

ADVANTAGES

- Exceptional adherence
- Durable anti-rust protection
- Interior & exterior
- Acts as a barrier against soot, water, nicotine stains, and more.
- Low odour for alkyd based



TECHNICAL SPECIFICATIONS



2 H
TO RECOAT



COVERAGE
600-700 FT²



FINISH	Mat	VOC VOLATILE ORGANIC COMPOUNDS	< 250 g/L before adding colorants
GLOSS	0-2°	SOLIDS BY VOLUME	51-54%
DILUENT	Mineral spirits	TOOLS	5 mm or 10 mm
BINDER	Alkyd	FORMULA	Stain killer primer
DRYING TIME	2 hours to recoat	ENVIRONMENT	Interior & exterior
COVERAGE	± 56-65 m ² (600-700 ft ²) by 3.78 L	APPLICATION TEMPERATURE	Between 10°C (50°F) and 30°C (86°F)

NOTES

Use only in a well-ventilated area. Protect from freezing.

SAFETY MESURES

Use only in a well-ventilated area. Do not thin. Keep container closed when not in use. In case of spillage, absorb with inert absorbent material and dispose of in accordance with local regulations. Wash thoroughly after handling. Use adequate protection equipment. Keep away from children.

FIRST AID

If swallowed, immediately contact a poison control centre or a physician. In case of contact with eyes or skin, rinse thoroughly with water.

WARNINGS

Instructions apply to most applications. However, they may not include certain conditions, application techniques, or special surfaces. If you have any questions, consult your retailer or test on a small surface.

WARRANTY

We certify that our products are of the highest quality and that the information in this document is provided in good faith. However, because we do not control the conditions of application and surface preparation, the guarantee is limited to the product's purchase price.

WASTE DISPOSAL

Use completely or dispose of leftovers at your local recycling centre. Leftovers can also be returned to your local retailer for proper disposal.

ULTRA PRIME

TECHNICAL DATA SHEET | CANAC ULTRA PRIME 967-031

SURFACE TYPES

Recommended for new, already painted or varnished interior and exterior surfaces. Can be applied on new gypsum board, new dry plaster, plaster repairs, masonry, and wood. Also acts as anti-rust primer on metal surfaces.

SURFACE PREPARATION TIPS

Surfaces to be painted must be dry, clean, free of dirt, dust, grease, oil, wax, scaling paint. Glossy areas should be dulled. Remove wall covering if there is evidence of bleeding colours.

Chipped or cracked coatings must be scraped and removed before application. Holes and cracks must first be repaired with a compound adapted to the surface. For better results, especially on rebellious stains or absorbent and porous repairs, apply two coats. Do not forget to cover surfaces that do not require painting.

Allow 15 to 30 days for new stucco, plaster, and masonry to cure before painting. Wait up to 7 days for plaster on new gypsum board.

APPLICATION PROCEDURE

Use product when surface temperature is above 10°C (50°F). Stir thoroughly before and during use. Apply primer after filling le remplissage holes, cracks or any other surface imperfections. Apply generously from unpainted area toward freshly painted area. This product can be applied by brush, roller or spray.

To do during application

- Mix containers together to ensure uniform colour, and mix well before and during application.

Do not

- Do not apply under direct sunlight.
- Do not apply if the surface is hot to the touch.
- Do not paint a humid surface.
- Do not dilute the product.

TECHNICAL ASSISTANCE

For more information or technical assistance contact your nearest Canac authorized retailer or visit www.studiochromatic.ca

FABRICATION

Made in Canada and packaged exclusively for Canac:
8620 Pascal Gagnon Street, Saint-Léonard QC H1P 1Z1, Canada
514 328-2727

In case of discrepancy between the information on the product and this datasheet, the data sheet will always prevail.



RECOMMENDED PRIMER

Canac Ultra Prime Stain killer (# 967-031) is a primer-sealer, undercoat, and stains resistant.

CLEANING TOOLS

Clean with mineral spirits. Clean tools immediately after use.

CONDITIONS

Temperature : 10°C to 25°C
Relative humidity : 25% to 50%

DRYING

Allow it to dry 1h to recoat. Allow 15 to 30 days for new stucco, plaster, and masonry to cure before painting. You could have to double the time if level of humidity is superior from 50% or the temperature is lower than 18°C

COVERAGE

Approximately 600-700 ft² (56-65 m²) per 3.78 L, depending on the porosity and texture of the substrate and if colorants were added or not.