

Isobutane Propane

Energy efficiency since 1985	DATE & VERSION – J	JANUARY 06, 2021 VERSION 02		
SAFETY DATA SH	IEET (SDS)			
Section 1. Identi	ification			
Product identifier CCB-200 AEROSOL				
Other means of identification 790460				
Recommended use and restrictions on use SUPER POWERFUL CLEAN	IER/DEGREASER/AEROSOL			
Initial supplier identifier PROLAB TECHNOLUB INC. 4531 RUE	INDUSTRIELLE, THETFORD MI	INES, (QUEBEC), G6H 2J1,		
CANADA TEL. (418) 423-2777 FAX : (418)				
	24 hour number 613-996-6666			
Section 2. Hazard id	lentification			
Classification of hazardous product (name of the category or subcategory				
Extremely flammable aerosol (Category 1)	,			
Gas under pressure (compressed gas)				
Skin irritation (Category 2)				
Eye irritation (Category 2A)				
Aspiration hazard (Category 1)				
Specific target organ toxicity - single exposure (Category 3), Central nervous	system			
Reproductive toxicity (Category 2)				
Specific target organ toxicity - repeated exposure (Category 2)				
Information elements (symbols, signal words, hazard statements and prec	cautionary statements of the categor	ry/subcategory)		
Danger				
H222 Extremely flammable aerosol.				
H229 Pressurized container: may burst if heated.				
H280 Contains gas under pressure; may explode if heated.				
H304 May be fatal if swallowed and enters airways.				
H315 Causes skin irritation.				
H319 Causes serious eye irritation.				
H336 May cause drowsiness or dizziness.				
H361 Suspected of damaging fertility or the unborn child.				
H373 May cause damage to organs through prolonged or repeated exposure.				
*** May displace oxygen and cause rapid suffocation. P201 Obtain special in				
have been read and understood. P210 Keep away from heat, hot surfaces, sparl				
spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing				
should not be allowed out of the workplace. P280 Wear protective gloves/ SWALLOWED: Immediately call a doctor. P331 DO NOT INDUCE VOMITI minutes. P332 + P313 If skin irritation occurs: Get medical attention. P333 P362+P364 Take off contaminated clothing and wash it before reuse. P305	protective clothing/ eye protection/ ± ING. P302+P352 IF ON SKIN, Wash 3 + P313 IF SKIN irritation or rash	face protection. P301+P310 IF with plenty of water for several occurs: Get medical attention.		
minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		-		
P340 IF INHALED: Remove person to fresh air and keep comfortable for brea	thing, P312 Call a doctor if you feel u	anwell. $P308 + P313$ IF exposed		
or concerned: Get medical attention. P410+P412+P403+P233 Protect from su				
in a well-ventilated area. Keep container tightly closed. P405 Store locked up.				
with local, regional or national regulations.				
	is a simple asphyxiant***			
Section 3. Composition/inform				
· · · · · · · · · · · · · · · · · · ·		Concentration (9/)		
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)		
Heptane/Naphtha	426260-76-6/64742-89-8	< 40		
Acetone         67-64-1         < 60           Xylenes         1330-20-7         < 40				
Xylenes	< 40			
Cyclohexane	110-82-7	< 4		
Toluene	108-88-3	< 2		
Ethylbenzene         100-41-4         < 7           Isobutane         75.28.5         < 10				
ISODUTADA		< 10		

75-28-5

74-98-6

< 10

< 13



	Section 4. First-aid measures		
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.		
Ingestion	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is		
	rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses		
	of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.		
Skin contact	IF ON SKIN, Wash with plenty of water for several minutes (15-20). If skin irritation occurs: Get medical attention.		
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue		
	rinsing. If eye irritation persists: Get medical attention.		
	symptoms and effects (acute or delayed) May be harmful if swallowed and enters airways.		
Indication of im	<b>mediate medical attention/special treatment</b> In all cases, call a doctor. Do not forget this document.		
	Section 5. Fire-fighting measures		
	s of the hazardous product (hazardous combustion products)		
	nd other irritant/toxic gases and fumes.		
	suitable extinguishing media		
In case of fire: U	se carbon dioxide, chemical powder agent and appropriate foam to extinguish.		
	ve equipment and precautions for fire-fighters		
	itating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper		
	nent and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans.		
Move containers	from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.		
	Section 6. Accidental release measures		
	itions, protective equipment and emergency procedures		
	area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should		
wear the appropri	iate protective equipment (See Section 8).		
	aterials for containment and cleaning up		
Avoid release to	the environment. Collect spillage. Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled		
	e with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material		
may pose the san	ne hazards as the spilled product. Notify the appropriate authorities as required.		
	Section 7. Handling and storage		
Precautions for			
Protect from sun	light. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from heat/sparks/open flames/hot surfaces No smoking.		
	an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash		
hands/nails/face	thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear gloves/protective		
clothing/eye prot	tection/face protection.		
	, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene		
	ng followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers		
	for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid		
contact with eyes			
away from incom	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep		
Section 8.	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to		
Section 8. Conditions for s	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities		
Section 8. Conditions for s Store in a well-v	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10).		
Section 8. Conditions for s Store in a well-v Inspect all incor	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of		
Section 8. Conditions for s Store in a well-v Inspect all incor	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. Section 8. Exposure controls/Personal protection		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parameter	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values)		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits:	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values) CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-ST	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH –		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> <pre>rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values) CAS 74-98-6 &amp; 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) &amp; PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm &amp; PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV-</pre>		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm &	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> entilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV- PEL-TWA 100 ppm;		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control paramo Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> entilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV- PEL-TWA 100 ppm; <b>gineering controls</b>		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control paramo Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> Tentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). In ing containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection ters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV-PEL-TWA 100 ppm; <b>gineering controls</b> rentilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control paramo Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make emo	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> Tentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 5000 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV-PEL-TWA 100 ppm; <b>gineering controls</b> rentilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure ergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make emo	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> Tentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection Exters (biological limit values or exposure limit values and source of those values) CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 5000 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV- PEL-TWA 100 ppm; gineering controls rentilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure ergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. ection measures/personal protective equipment		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make em Individual prote	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities entilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values) CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 130-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV- PEL-TWA 100 ppm; gineering controls entilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure ergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. ection measures/personal protective equipment ection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits.		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make eme Individual prote are unknown. Ch	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to safe storage, including any incompatibilities entilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks.  Section 8. Exposure controls/Personal protection eters (biological limit values or exposure limit values and source of those values) CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 110-41-4 ACGIH – TLV- PEL-TWA 100 ppm; gineering controls ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure ergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area. ection measures/personal protective equipment ection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits the emically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make em Individual prote are unknown. Ch during all handli	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> rentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection Section 9. Sect</b>		
Section 8. Conditions for s Store in a well-v Inspect all incor obstruction and a Control parame Exposure limits: ppm & TLV-STI TLV-TWA 100 TWA 20 ppm & Appropriate en Use under well-v limits. Make eme Individual prote are unknown. Ch during all handli after handling. E	s, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep npatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to <b>safe storage, including any incompatibilities</b> Tentilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). ning containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of accessible only to trained personnel. Inspect periodically for damage or leaks. <b>Section 8. Exposure controls/Personal protection Exters (biological limit values or exposure limit values and source of those values)</b> CAS 74-98-6 & 75-28-5 – ACGIH – TLV-TWA (STEL) and/or PEL-TWA 1000 ppm; CAS 67-64-1 – ACGIH – TLV-TWA 500 EL 750 ppm; CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 110-82-7 – ACGIH – ppm; CAS 108-88-3 – ACGIH – TLV-TWA 20 ppm & PEL-TWA 200 ppm (ceiling 300 ppm); CAS 100-41-4 ACGIH – TLV- PEL-TWA 100 ppm; <b>gineering controls rentilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure ergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.</b>		



Section 9. Physical and chemical properties							
Appearance, physical state/colour	Clear liqu	id (aerosol)	Vapour	pressure	Not availa	able	
Odour Characteristic			Vapour	density	Heavier th	han air	
Odour threshold Not available		Relative density 0.68-0.77					
pH Not available			Solubili	ty Not av	vailable		
Melting/freezing point Not availa	able		Partitio	n coefficien	t - n-octan	ol/water	Not available
<b>Initial boiling point/range</b> 56°C			Auto-ig	nition temp	erature	Not availa	ble
<b>Flash point</b> ~ -10°C Closed cup (flat	ume projectio	on > 15 cm & no	Decomp	osition tem	perature	Not avai	lable
flashback)							
<b>Evaporation rate</b> Not available			Viscosit	y Not ava	ulable		
Flammability (solids and gases) Ex	xtremely flat	mmable aerosol	VOC Not available				
Upper and lower flammability/explos	sive limits	Not available	Other	None know	wn		
		Section 10. Stability	and read	ctivity			
Reactivity							
Does not react under the recommended s	storage and l	nandling conditions prescri	bed.				
Chemical stability		<b></b>					
Stable under the recommended storage a	and handling	conditions prescribed.					
Possibility of hazardous reactions							
Accumulation of flammable if product	t is heated. I	Do not spray on an open f	flame or o	ther ignition	n source. D	o not pier	ce or burn, even after use.
Protect from sunlight. Do not expose to				C			
Conditions to avoid (static discharge,	, shock or v	ibration)					
Keep away from heat, hot surfaces, spa	arks, open fl	ames and other ignition so	ources. No	o smoking. l	Do not spra	y on an op	ben flame or other ignition
source. Do not pierce or burn, even afte	er use. Prote	ct from sunlight. Do not e	xpose to te	emperatures	exceeding	50 °C/122	°F.
Incompatible materials							
Oxidizing materials; etc.							
Hazardous decomposition products							
None known							
		Section 11. Toxicologi	cal infor	mation			
Information on the likely routes of ex							
May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May displace oxygen and cause rapid suffocation.							
Symptoms related to the physical, chemical and toxicological characteristics							
Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.							
Delayed and immediate effects (chron	nic effects f	rom short-term and long	g-term exp	oosure)			
Skin Sensitization – No data available;							
Respiratory Sensitization – No data available;							
Germ Cell Mutagenicity – No data available;							
Carcinogenicity – No ingredient listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – Possible;							
Specific Target Organ Toxicity — Single Exposure – Central nervous system;							
Specific Target Organ Toxicity — Repeated Exposure – Possible;							
Aspiration Hazard – Possible;							
Health Hazards Not Otherwise Classified – No data available.							
Numerical measures of toxicity (ATE; LD <sub>50</sub> & LC <sub>50</sub> )							
CAS 75-28-5 LC <sub>50</sub> 658000 mg/m <sup>3</sup> 4 hrs (rat); CAS 67-64-1 LD <sub>50</sub> Oral - Rat - 5,800 mg/kg; LC <sub>50</sub> Inhalation - Rat - 8 h - 50100 mg/m <sup>3</sup> ; CAS 1330-							
20-7 Oral, rat LD <sub>50</sub> 4300 mg/kg; Derma							
4H; CAS 108-88-3 LD <sub>50</sub> Oral - Rat - 5			h – 8000 j	ppm; LD50 I	Dermal - Ra	abbit – 121	125 mg/kg; CAS 100-41-4
Oral, rat LD <sub>50</sub> 3500 mg/kg; Dermal, rabbit LD <sub>50</sub> 15380 mg/kg;							
ATE not available in this document.							
		Section 12. Ecologica					
Ecotoxicity (aquatic and terrestrial information) No data available for this product.							
Persistence and degradability         No data available for this product.							
Bioaccumulative potential No data available for this product.							
Mobility in soil         No data available for this product.							
Other adverse effects No data ava	ulable						
Section 13. Disposal considerations							
Information on safe handling for disposal/methods of disposal/contaminated packaging							

Dispose of contents/container into safe container in accordance with local, regional or national regulations.



Section 14. Transport information				
UN number; Pr	oper shipping name; Class(es	;); Packing group (PG) of the TDG Regulations		
UN1950; AERO	SOLS; CLASS 2.1			
UN number; Pr	oper shipping name; Class(es	;); Packing group (PG) of the IMDG (maritime)		
	SOLS; CLASS 2.1			
UN number: Pr	oper shipping name: Class(es	); Packing group (PG) of the IATA (air)		
	SOLS, FLAMMABLE; CLAS			
	Special precautions May also be shipped as a LIMITED QUANTITY in accordance with TDG.			
	transport/conveyance)			
	hazards (IMDG or other)	None		
	(usually more than 450 L in c			
buik transport	(usually more than 450 E m e	Section 15. Regulatory information		
Safety/health Canadian regulations specifics		with the hazard criteria of the Hazardous Products Regulations (HPR).		
	vironmental outside regulati			
		is regulated according to OSHA (29 CFR).		
		Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.		
	CSA information: Refer to the i	igredients listed in Section 3.		
	otection Association (NFPA):			
HEALTH: 1 FLAMMABILITY: 4 INSTABILITY: 1 SPECIAL HAZARDS: Refer to Section 2 & 3.				
	E: 0 = Minimal  1 = Slight			
California Propos	sition 65: This product contains	a material known to the State of California to cause cancer or other reproductive harm.		
Section 16. Other information				
	st revision of the safety data s			
References	Safety Data Sheets from manu	facturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.		
Abbreviations				
ACGIH		ernmental Industrial Hygienists		
ATE	Acute toxicity estimate			
CAS	Chemical Abstract Service			
DSL	Domestic Substance List			
IARC	International Agency for Research on Cancer			
IATA	International Air Transport Association			
IMDG	International Maritime Dangerous Goods Code			
LC	Lethal concentration			
LD	Lethal Dosage			
NIOSH	National Institute for Occupational Safety and Health			
NTP	National Toxicology Program (U.S.A.)			
OSHA	Occupational Safety and Health Administration (U.S.A.)			
PEL	Permissible Exposure Limit			
STEL	Short-term Exposure Limit			
TDG	Transport of dangerous goods in Canada			
TLV	Threshold Limit Value			
TSCA	Toxic Substances Control Act			
TWA	Time Weighted Average			
WHMIS				
The information presented herein has been compiled from sources considered dependable and is accurate to the best of PROLAB TECHNOLUB INC.'s				
knowledge. PROLAB TECHNOLUB INC. Makes no warranty whatever expresses or implied of merchantability or fitness for the particular purpose.				
The information relates only to the specific material designated herein and does not relate to use in combination with any other material or in any				

process. Customers are encouraged to conduct their own tests. Before using the product, read its label. **PROLAB TECHNOLUB INC.** Assumes no responsibility for injury to recipient or to third persons or for any damage to any property and recipient assumes all such risks.