

KITCHEN ZONE™

Square Lay-in
smooth texture




CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Kitchen Zone 24" x 24" panels with Prelude XL 15/16" suspension system

Panels meet USDA/FSIS guidelines. A better option than vinyl-covered gypsum; panels offers a lower cost, lighter weight option, with more pieces per carton.

KEY SELECTION ATTRIBUTES

-  Kitchen Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Easier to cut with less dust
- Recyclable through Armstrong Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

COLOR



White
(WH)

DETAILS



- Kitchen Zone™ Lay-in
- Kitchen Zone™ Lay-in with Prelude® 15/16" suspension system

KITCHEN ZONE™

Square Lay-in
smooth texture



LEED® WELL | LBC

UP TO 36% RECYCLED CONTENT

energy management construction waste mgmt regional materials design for flexibility EPD recyclable/ bio-based materials recycled content sourcing of raw materials material ingredient reporting low emitting/ materials lighting quality acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
KITCHEN ZONE™	1	673	24 × 24 × 5/8"
15/16" Square Lay-in			
		672	24 × 48 × 5/8"


PERFORMANCE SELECTION

Dots represent high level of performance.

NRC + CAC =		Total Acoustics¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program	30-Yr Warranty
N/A	33	N/A	Class A	0.89	*	*	*	*	*	*	*	*	*	*	*
N/A	33	N/A	Class A	0.89	*	*	*	*	*	*	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less.

ASTM E1264 Classification
Type A, Form A2.2, Pattern G; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Application Consideration
Not designed for use in close proximity to commercial grease ducts.

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
672 – 0.67 LBS/SF; 96 SF/CTN
673 – 0.82 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton