

Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3	Revis	ion Date: 02/20/2020	Print Date: 05/04/2020
GHS classification in accordance SECTION 1. PRODUCT AND C		Hazardous Products Regulations (IDENTIFICATION	
Product identifier Trade name Product code	:	Valvoline™ Full Synthetic Advanced SAE	5W-20 Motor Oil
Details of the supplier of the sheet Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL (1-800-832		v dataEmergency telephone numbe 1-800-VALVOLINE (1-800-825- Regulatory Information Numb 1-800-TEAMVAL (1-800-832-68)Product Information 1-800-TEAMVAL (1-800-832-68)	8654) er 325)
SDS@valvoline.com			

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Not a hazardous substance or mixture. **GHS** label elements Not a hazardous substance or mixture. Other hazards None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Classification	Concentration (%)
64742-54-7	Asp. Tox. 1; H304	>=30.00 - < 60.00
		>=1.00 - < 5.00
6	4742-54-7 4742-54-7	4742-54-7 Asp. Tox. 1; H304

Actual concentration or concentration range is withheld as a trade secret



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3	Revision Date: 02/20/2020	Print Date: 05/04/2020
SECTION 4. FIRST AID MEASU	RES	
General advice	: No hazards which require special first aid measures	».
If inhaled	 If breathed in, move person into fresh air. If unconscious, place in recovery position and seek advice. If symptoms persist, call a physician. 	medical
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by w with soap and water.	ashing
In case of eye contact	: Remove contact lenses. Protect unharmed eye.	
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious per If symptoms persist, call a physician.	erson.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected.	
Notes to physician	: No hazards which require special first aid measures	5.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	 Do not allow run-off from fire fighting to enter drains or water courses. If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Hazardous combustion products	: carbon dioxide and carbon monoxide
Specific extinguishing methods	:



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3	Revision Date: 02/20/2020	Print Date: 05/04/2020
	Product is compatible with standard fire-figh	ting agents.
Further information	: Standard procedure for chemical fires.	
Special protective equipment for firefighters	: In the event of fire, wear self-contained brea	athing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	: Prevent further leakage or spillage if safe to do so.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
Other information	: Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (Petroleum), Hydrotreated Heavy Paraffir	64742-54-7 nic	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL



Valvoline[™] Full Synthetic Advanced SAE 5W-20 Motor Oil

rsion: 1.3	Revision Date:			Print Da 05/04/20
		TWA	1 mg/m3 Mist	CA BC OE
DISTILLATES (PETROLEUM) HYDROTREATED HEAVY PARAFFINIC	, 64742-54-7	TWA	5 mg/m3 Mist	CA AB OE
		STEL	10 mg/m3 Mist	CA AB OE
		TWAEV	5 mg/m3 Mist	CA QC OE
		STEV	10 mg/m3 Mist	CA QC OE
		TWA	1 mg/m3 Mist	CA BC OE
Engineering measures	conditions c exist, provic exhaust) ve guidelines (of use. Howeve le sufficient me ntilation to mai	hould be adequate er, if unusual operat echanical (general a ntain exposure belo r below levels that c verse effects.	ing conditions nd/or local w exposure
Personal protective equipme Respiratory protection		l respiratory pro	otective equipment	normally
Eye protection		proof safety goggles if material could be misted or splashed		
Skin and body protection	Safety shoe	Wear as appropriate: Safety shoes Wear resistant gloves (consult your safety equipment supplier).		
Hygiene measures	: General ind	ustrial hygiene	practice.	
CTION 9. PHYSICAL AND CHI	EMICAL PROPE	RTIES		
Appearance	: liquid			
Colour	: amber			
Odour	: mild			
Odour Threshold	: No data av	ailable		
рН	: No data av	ailable		



SAFETY DATA SHEET

Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3		vision Date: 02/20/2020	Print Date: 05/04/2020
Boiling point/boiling range	:	estimated 330 °C	
Flash point	:	> 199 °C	
		Method: closed cup	
Evaporation rate	:	< 1 Ethyl Ether	
Flammability (solid, gas)	:	No data available	
Self-ignition	:	No data available	
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit	
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit	
Vapour pressure	:	0.1333333 hPa (20 °C) Calculated Vapor Pressure	
Relative vapour density	:	> 1 AIR=1	
Relative density	:	No data available	
Density	:	0.849 g/cm3	
Solubility(ies) Water solubility	:	No data available	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	ca. 50 mm2/s (40 °C)	
Oxidizing properties	:	No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3	Revision Date: 02/20/2020	Print Date: 05/04/2020
Chemical stability	: Stable under recommended storage conditions.	
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization	
Conditions to avoid	: None known.	
Incompatible materials	: Strong oxidizing agents	
Hazardous decomposition products	No hazardous decomposition products are known.	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of Inhalation Skin contact Eye Contact Ingestion Acute toxicity Not classified based on available <u>Components:</u> Distillates (Petroleum), Hydrot	e information.
Acute oral toxicity :	LD50 (Rat): > 15 g/kg
Acute dermal toxicity :	LD50 (Rabbit): > 5 g/kg
DISTILLATES (PETROLEUM), I Acute oral toxicity :	HYDROTREATED HEAVY PARAFFINIC: LD50 (Rat): > 15 g/kg
Acute dermal toxicity :	LD50 (Rabbit): > 5 g/kg
Skin corrosion/irritation Not classified based on available <u>Components:</u> Distillates (Petroleum), Hydrot Assessment : Result :	
	HYDROTREATED HEAVY PARAFFINIC: Slight, transient irritation Slight, transient irritation
Serious eye damage/eye irritat Not classified based on available <u>Product:</u> Remarks	



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

sion: 1.3	Revision Date: 02/20/2020	Print Dat 05/04/202
Components:	· · · · · · · · · · · · · · · · · · ·	
· ·), Hydrotreated Heavy Paraffinic:	
Result	: No eye irritation	
Assessment	: No eye irritation	
DISTILLATES (PETRO	DLEUM), HYDROTREATED HEAVY PARAFFINIC:	:
Result	: No eye irritation	
Assessment	: No eye irritation	
Respiratory or skin s	ensitisation	
Skin sensitisation	and a first to the forest of the second s	
Not classified based or		
Respiratory sensitisa		
Not classified based or		
Germ cell mutagenici		
Not classified based or	available information.	
Carcinogenicity	a voilable information	
Not classified based or		
Components:	DLEUM), HYDROTREATED HEAVY PARAFFINIC:	
A		
Assessment	: Classified based on DMSO extract conto (EC) 1272/2008, Annex VI, Part 3, Note	
Assessment	(LC) 1272/2000, Annex VI, 1 at 3, Note	L)
Reproductive toxicity	,	
Not classified based or		
STOT - single exposu	ire	
Not classified based or		
STOT - repeated expo		
Not classified based or		
Aspiration toxicity		
Not classified based or	n available information.	
Draduat		
Product:	lassification	
No aspiration toxicity c	เสริงแบสแบบ	
Components:		
), Hydrotreated Heavy Paraffinic:	
May be fatal if swallow		
,		
	DLEUM), HYDROTREATED HEAVY PARAFFINIC:	:
No aspiration toxicity c	lassification	
Further information		
Further information		
Further information <u>Product:</u> Remarks	: No data available	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity Product:



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3	Revision Date: 02/20/2020	Print Date: 05/04/2020
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.	
Long-term (chronic) aquatic hazard	: Not classified based on available information.	
<u>Components:</u> Distillates (Petroleum), Hydrot Toxicity to fish	reated Heavy Paraffinic: : LL50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h	
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h	
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l	
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.	
Long-term (chronic) aquatic hazard	: Not classified based on available information.	
DISTILLATES (PETROLEUM) Toxicity to fish	, HYDROTREATED HEAVY PARAFFINIC: : LL50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h	
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h	
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l	
Ecotoxicology Assessment Short-term (acute) aquatic	: Not classified based on available information.	



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

sion: 1.3	Revision Date: 02/20/2020	Print Date: 05/04/2020
hazard		
Long-term (chronic) aqu hazard	uatic : Not classified based on available information	n.
Persistence and degra	adability	
Components:		
No data available Bioaccumulative pote	ntial	
Components:	IIIIai	
	LEUM), HYDROTREATED HEAVY PARAFFINIC:	
Partition coefficient: n-		
octanol/water		
No data available		
Mobility in soil		
Components:		
No data available		
Other adverse effects		
No data available		
Product:	: No data available	
Additional ecological information		
Components:		

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.



Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Version: 1.3

Revision Date: 02/20/2020

Print Date: 05/04/2020

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:DSL:All components of this product are on the Canadian DSL					
AICS	:	On the inventory, or in compliance with the inventory			
ENCS	:	On the inventory, or in compliance with the inventory			
KECI	:	On the inventory, or in compliance with the inventory			
IECSC	:	q (quantity restricted)			
PICCS	:	On the inventory, or in compliance with the inventory			
TCSI	:	On the inventory, or in compliance with the inventory			
TSCA	:	On TSCA Inventory			

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information Internal information : R0396047

NFPA:

HMIS III:




Version: 1.3

Health

SAFETY DATA SHEET

Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil



Special hazard

0

0

HEALTH0FLAMMABILITY1PHYSICAL HAZARD0

Print Date: 05/04/2020

0 = not significant, 1 =Slight, 2 = Moderate, 3 = High

4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

nstability

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Revision Date: 02/20/2020

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"



Version: 1.3

SAFETY DATA SHEET

Valvoline™ Full Synthetic Advanced SAE 5W-20 Motor Oil

Print Date:

		05/04/2020
ISO : International O logPow : octanol-wat LCxx : Lethal Concer LDxx : Lethal Dose, f ICxx : Inhibitory Conc Ecxx : Effective Conc N.O.S.: Not Otherwis OECD : Organization OEL : Occupational B P-Statement : Precas	se Specified for Economic Co-operation and Development Exposure Limit utionary Statement paccumulative and Toxic ective Equipment	05/04/2020
STEL : Short-term ex STOT : Specific Targ	kposure limit jet Organ Toxicity	
TLV : Threshold Limi TWA : Time-weighter vPvB : Very Persister	it Value d average nt and Very Bioaccumulative	
WEL : Workplace Ex	posure Level	

Revision Date: 02/20/2020

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System NFPA : National Fire Protection Association NIOSH : National Institute for Occupational Safety and Health OSHA : Occupational Safety and Health Administration PMRA : Health Canada Pest Management Regulatory Agency RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System