

PEBBLE™  
Square Lay-in  
medium texture

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



Pebble panel with Prelude XL 15/16" suspension system

Economical, medium-textured panels have an easy-to-clean, durable surface with high sound absorption options.

KEY SELECTION ATTRIBUTES

- High sound absorption - up to 0.80 NRC (perforated panels only)
- Easy-to-clean, durable surface - Impact-, Scratch-, and Soil-resistant, and scrubbable
- Economical solution
- Mold- and mildew-resistant surface
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



White  
(WH)

DETAILS



1. Pebble™
2. Pebble™ with Prelude® XL® 15/16" suspension system

# PEBBLE™

## Square Lay-in medium texture

LEED® WELL™ LBC

UP TO 71% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/ biodegradable producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting/ materials

lighting quality






acoustics

Calculate sustainability with Ecomedes

armstrongceilings.com/ecomedes

LOCATION DEPENDENT

### VISUAL SELECTION


armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
PEBBLE™ High NRC (Perforated)	1	2988	24 × 24 × 1"	
15/16" Square Lay-in		2989	24 × 48 × 1"	
1" Thick – 15/16" Square Lay-in				
Made-to-Order Sizes			Width	Length
PEBBLE™ High NRC (Perforated)			12" - 30"	12" - 60"
PEBBLE™ (Perforated)	1	2983	24 × 48 × 5/8"	
15/16" Square Lay-in		2970	24 × 60 × 5/8"	
PEBBLE™ (Perforated and Unperforated)	1	2968	24 × 48 × 5/8"	
15/16" Square Lay-in				
5/8" Thick – 15/16" Square Lay-in				
Made-to-Order Sizes			Width	Length
PEBBLE™ (Unperforated)			12" - 30"	12" - 60"

3-4 WEEKS  
order to ship

3-4 WEEKS  
order to ship

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

### SUSPENSION SYSTEM



### PHYSICAL DATA

**Material**  
Fiberglass with vinyl facing

**Surface Finish**  
Scrubable vinyl film facing (UV protected)

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type B, Form B3, Pattern F; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Acoustical Details**  
A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

**Insulation Value**  
2968, 2970, 2983 - R Factor - 2.6 (BTU units)  
R Factor - 0.46 (Watts units)  
2988, 2989 - R Factor - 4.0 (BTU units)  
R Factor - 0.70 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
2968, 2983 – 0.20 LBS/SF; 128 SF/CTN  
2970 – 0.20 LBS/SF; 120 SF/CTN  
2988, 2989 – 0.31 LBS/SF; 80 SF/CTN

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels.

**Metric Items Available**  
2983M, 2970M, 2988M, 2989M, 2968M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

